

MPPC[®] (Multi-Pixel Photon Counter) arrays



S13363-3050NE-16

MPPC arrays in a chip size package miniaturized through the adoption of TSV structure

The S13363-3050NE-16 is a miniaturized one-dimensional 16 ch MPPC array using TSV (through-silicon via) and CSP (chip size package) technologies. The product has an effective photosensitive area of 3×3 mm per channel. The gap between channels is narrowed and the dead area is reduced. This is suitable for applications, such as nuclear medical, non-destructive inspection, and high energy physics experiment, that require photon counting measurement.

Features

- Applications

- Low crosstalk
- Low afterpulses
- Low voltage (VBR=53 V typ.) operation
- \blacksquare High gain: 1.7 \times 10⁶ typ.

High energy physics experiment

- Nuclear medicine
- Muon tomography
- Flow cytometry

Structure

Parameter	Specification		
Number of channels	16	-	
Effective photosensitive area/channel	3 × 3	mm	
Pixel pitch	50	μm	
Number of pixels/channel	3584	-	
Fill factor	74	%	
Package	Glass epoxy	-	
Seal material	Epoxy resin	-	
Refractive index of window material	1.55	-	

Absolute maximum ratings

Parameter	Symbol	Condition	Value	Unit
Operating temperature ^{*1}	Topr	No dew condensation ^{*1}	-20 to +60	°C
Storage temperature*1	Tstg	No dew condensation ^{*1}	-20 to +80	°C
Soldering temperature	Tsol		240 (twice)* ²	°C

*1: When there is a temperature difference between a product and the surrounding area in high humidity environments, dew condensation may occur on the product surface. Dew condensation on the product may cause deterioration in characteristics and reliability.

*2: Reflow soldering, JEDEC J-STD-020 MSL 5a, see P.5

Note: Exceeding the absolute maximum ratings even momentarily may cause a drop in product quality. Always be sure to use the product within the absolute maximum ratings.

Electrical and optical characteristics (Typ. Ta=25 °C, unless otherwise noted)

Parameter		Symbol	Condition Value		Unit
Spectral response range λ		λ		320 to 900	nm
Peak sensitivity wavelength		λр	450		nm
Photon detection efficiency PDE		λ=λp, VR=Vop	40	%	
Breakdown voltage	kdown voltage VBR			53 ± 5	V
Recommended operating volt	Recommended operating voltage Vop			VBR + 3	V
Vop variation between	Тур.	<mark>ρ.</mark> ΔVop	VR=Vop	0.1	v
channels in one product	Max.			0.3	
Dark count rate	Тур.	DCR	VR=Vop	0.5	Mana
	Max.			1.5	meps
Terminal capacitance		Ct	VR=Vop, f=100 kHz	320	pF
Gain		М	VR=Vop 1.7 × 10 ⁶		-
Temperature coefficient of recommended operating voltage		ΔTVop		54	mV/°C

*3: Photon detection efficiency does not include crosstalk and afterpulses. *4: Refer to the data attached to each product.

Photon detection efficiency vs. wavelength (typical example)



Photon detection efficiency does not include crosstalk and afterpulses.





- Overvoltage vs. gain, crosstalk probability, photon detection efficiency (typical example)

MPPC characteristics vary with the operating voltage. Although increasing the operating voltage improves the photon detection efficiency and time resolution, it also increases the dark count and crosstalk at the same time, so an optimum operating voltage must be selected to match the application.



Dimensional outline (unit: mm)



* Distance from package top to photosensitive surface

KAPDA0220EA

Pad no.	Connection						
1	A (ch 1)	9	A (ch 5)	17	A (ch 9)	25	A (ch 13)
2	K (ch 1)	10	K (ch 5)	18	K (ch 9)	26	K (ch 13)
3	A (ch 2)	11	A (ch 6)	19	A (ch 10)	27	A (ch 14)
4	K (ch 2)	12	K (ch 6)	20	K (ch 10)	28	K (ch 14)
5	A (ch 3)	13	A (ch 7)	21	A (ch 11)	29	A (ch 15)
6	K (ch 3)	14	K (ch 7)	22	K (ch 11)	30	K (ch 15)
7	A (ch 4)	15	A (ch 8)	23	A (ch 12)	31	A (ch 16)
8	K (ch 4)	16	K (ch 8)	24	K (ch 12)	32	K (ch 16)

Note: A=Anode, K=Cathode

Recommended land pattern (unit: mm)





Recommended reflow soldering conditions



KSPDB0418EA

- This surface mount type package product supports lead-free soldering. After unpacking, store it in an environment at a temperature of 25 °C or less and a humidity of 60% or less, and perform soldering within 24 hours.
- The effect that the product receives during reflow soldering varies depending on the circuit board and reflow oven that are used. Before actual reflow soldering, check for any problems by testing out the reflow soldering methods in advance.
- When 12 or more months have passed or if the packing bag has not been stored in an environment described above, perform baking. For the baking method, see the related information "Precautions / Surface mount type products".

Precautions

- If necessary, incorporate appropriate protective circuits in power supplies, devices, and measuring instruments to prevent overvoltage and overcurrent.
- · This product may be damaged by partial force, so please handle with care.



Related products

Power supply for MPPC C11204 series

The C11204 series is a high voltage power supply that is optimized for driving MPPCs. Since it has a temperature compensation function, MPPCs can be driven stably even in environments subject to temperature changes.



Power supplies for MPPC lineup

Type no.	Package type	Temperature stability (ppm/°C)	Voltage boost circuit	MR (magnetic resonance) compatibility	Features
C11204-01	With leads	±10	Yes	-	High precision Low ripple noise
C11204-03	With leads	±10	-	Yes	MR compatible Low price
C11204-04	Surface mount	±30	-	Yes	MR compatible Low price Compact: 11.5 × 11.5 mm
C11204-12	Surface mount	±10	Yes	-	High precision Low ripple noise Compact: 11.5 × 11.5 mm

MPPC modules C13368-3050EA-16

The C13368-3050EA-16 is a photon counting module capable of detecting very low level light. This module consists of a 16 ch MPPC array, current-to-voltage coverter circuit, high-voltage power supply circuit, and temperature compensation circuit, etc.





Related information

www.hamamatsu.com/sp/ssd/doc_en.html

- Precautions
- Disclaimer
- · Precautions / Metal, ceramic, plastic package products
- Precautions / Surface mount type products

Catalogs

· Technical information / MPPC

MPPC is a registered trademark of Hamamatsu Photonics K.K. (EU, Japan, Korea, Switzerland, UK, U.S.A.)

Information described in this material is current as of March 2025.

Product specifications are subject to change without prior notice due to improvements or other reasons. This document has been carefully prepared and the information contained is believed to be accurate. In rare cases, however, there may be inaccuracies such as text errors. Before using these products, always contact us for the delivery specification sheet to check the latest specifications.

The product warranty is valid for one year after delivery and is limited to product repair or replacement for defects discovered and reported to us within that one year period. However, even if within the warranty period we accept absolutely no liability for any loss caused by natural disasters or improper product use. Copying or reprinting the contents described in this material in whole or in part is prohibited without our prior permission.



www.hamamatsu.com

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Chuo-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81)53-434-3311, Fax: (81)53-434-5184

1126-1 IChIno-Cho, Chuo-Ku, Hamamatsu City, 435-8558 Japan, Ielephone: (19)08-231-960, Fax: (19)08-231-1218 U.S.A.: HAMAMATSU PORTONICS DEUTSCHLAND GMBH: Arzbergerst. 10, 82211 Herrsching am Anmerse, Germany; Telephone: (19)88-231-218 Germany: HAMAMATSU PHOTONICS DEUTSCHLAND GMBH: Arzbergerst. 10, 82211 Herrsching am Anmerse, Germany; Telephone: (19)8152-375-0, Fax: (49)8152-265-8 E-mail: info@hamamatsu.de France: HAMAMATSU PHOTONICS FARNCE S.A.R.L: 19 Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France; Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10 E-mail: info@hamamatsu.de France: HAMAMATSU PHOTONICS FARNCE S.A.R.L: 19 Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France; Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10 E-mail: info@hamamatsu.de Ninted Kingdowin: HAMAMATSU PHOTONICS IN LIMITED: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordheire, AU 7 1BW, UK, Telephone: (44)1707-29488, Fax: (44)1707-252777 E-mail: info@hamamatsu.co.uk North Europe: HAMAMATSU PHOTONICS ITALIA S.R.L: Strada della Maia, 1 int. 6 20044 Arese (Milano), Italy, Telephone: (39)02-93 58 17 3, Fax: (39)02-93 58 17 4 E-mail: info@hamamatsu.dt China: HAMAMATSU PHOTONICS (CHINI VO, LTD: 2101, Tower B, Jiaming Center, 27 Dongsanhuan Bellu, Chaoyang District, 10020 Beljing, P.R. China, Telephone: (86)3-659-0080, Fax: (86)3-659-0081 E-mail: info@hamamatsu.co.uk Taiwan: HAMAMATSU PHOTONICS TALWAN CO, LTD: 13F-1, No.101, Section 2, Gongdao 5th Road, East Dist, Hsinchu City, 300046, Taiwan(R.O.C) Telephone: (886)3-659-0080, Fax: (880)3-659-0081 E-mail: info@hamamatsu.co.uk